

Twenty Four Seven Global

TECHNICAL DATA SHEET

Product name: Water Based Primer
Product code: 604.715
Brand Name: Emicoteï 3
Manufacturer: 24-7 Global Coatings Ltd
Location: Jarrow, UK.

Date: 04 May 2009
Version: 02

SPECIFICATIONS

Viscosity: 14 - 18 Sec. ISO 4 @ 25 DEG C
10 - 16 Sec. #4 Ford Cup @ 77 DEG F

INFORMATION

Description: A waterbased primer for use as a print receptive coating for digital printing. It may also be used as a size coat to enhance ink adhesion to difficult substrates.

Density: 1.05 . 1.15 Kg/L

Substrate: Papers, synthetics, metpols and foils.

Applied Colour: Water white

Thinner: Dilution not recommended

Cleanup Thinner: Water followed by most roller washes.

Application: Roller Coater, Anilox

Drying / Stoving: Air dried or hot air assisted.

Film Weight: 1.5 . 2.0GSM (Wet film weight).
Exceeding the recommended filmweight may affect the drying

Flashpoint: Not Flammable

Storage: Store in original container between 5 and 25 degrees centigrade.
Protect from frost and direct sun light.

Remarks: This is a press ready product, compatible with waterbased and free radical UV coatings.

The suggestions and/or recommendations for use and application given herein represent the best information available to us and are believed to be reliable. Since the application of our products however is made under conditions beyond our control, no warranty (either expressed or implied) is given with respect of these recommendations or our products or in relation to any quality or fitness for purpose requirements. Users of our products must satisfy themselves, by conducting confirmatory tests in order to determine final suitability or fitness for their own specific end uses.